

Product Data Sheet



ASMACO ZINC RICH COLD GALVANIZING SPRAY

Product Description:

Quick dry spray with special zinc dust, containing 99% pure zinc. Gives glossy finish and resist up to 550°C temperature without degrading and allowing it to be used on materials subject to be welded(except argon welding).Formulation guaranteed free from CFC.

Key Performance Properties:

- Galvanic protection against thermal and chemical corrosion.
- Resists salty and other corrosive atmospheres.
- Resists temperature from -50 to 550°C .
- High coverage ability without running or excessive thickness.
- Excellent finish.
- Tack free and handled in 10 to 15 minutes at 250C,full cured after 24 hour.
- Aerosol formulation gives quick, even spray
- Can be painted after curing
- CFC Free

Applications:

Electrical and signal posts, security rails, Chimney stacks, flanges, pipe work, connections, Heating and ventilating, equipment, Nails and screws before plastering, Sanitary installations, heat pump, air conditioning equipment, Railings, fences and doors

Typical Properties:

Appearance	Colored Liquid
Color	Metallic Silver
Odor	Solvent
Flash Point	Not Measurable
Specific Gravity @ 250C	0.995
Resistance to Brine	280 h unscratched film
Temperature Range	50 to 550°C
Surface dry at room temperature	5 to 8 minutes
Hard dry	1 hr.
Complete Curing	24 hr.
Health and Safety	Flammable



ASMACO ZINC RICH COLD GALVANIZING SPRAY

CFC Free

99% Pure Zinc

Product Data Sheet



Surface Preparation:

As far as possible, eliminate all traces of rust by brushing, sanding or shot blasting and traces of oil and dirt with cleaners, after that treated with IPA. Shake the spray can as well for at least 1 minute at every interval of use. Hold the can approximately 25 to 30 cm away from the object to be painted. If over coating ensure coating is completely dried.

Storage and Shelf Life:

12 months when stored at 21°C (70° F) / 50% relative humidity out of direct sunlight. do not expose to temperatures exceeding 50°C because the cans contain pressurized gas. It may burn above 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent materials. Keep out of reach of children.

Packaging:

Spray Paint is supplied as 12 cans / carton.

Shipping Limitations: None

Note

The information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application. Likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non – Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory Ltd's control, we can accept no liability for the result obtained. Anchor Allied Factory Ltd's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory Ltd will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.



مصنع انكور الايد ذ.م.م
ANCHOR ALLIED FACTORY L.L.C.

Tel. No.: +971 6 5342091, Fax No.: +971 6 5342107

P.O. Box No.: 21152, Sharjah (U.A.E.), E-mail : info@anchorallied.com.



SILICONE SEALANTS • WATERPROOFING COATINGS • PU SEALANTS • POLYSULPHIDE SEALANTS • ACRYLIC & DUCT SEALANTS
POLYURETHANE FOAM • SPRAY PAINT • SILVER CLOTH DUCT TAPE • CREPE PAPER MASKING TAPE • ALUMINIUM FOIL TAPE
P.E. PROTECTION TAPE • PVC PIPE WRAP TAPE • CONTACT ADHESIVE • EPOXY STEEL • PVC CEMENTS • SUPER GLUE

www.anchorallied.com